

TEST MONITOR

Testmonitor 7 Zoll

TEST Monitor

Testmonitor 7 Zoll

Panel Type Case Type Maximum Resolution

IP Camera Test

Co axial HD test Cable test function

Network Wi-Fi

Storage

Work Humidity Work Temperature

Power Off

7" Capacitive Touch Screen

Ruggedised Plastic

1920 (H) x 1200 (W)

IPC test, IPC viewer, Rapid Video, RTSP, ONVIF

Hik test tool, UNV test tool

Dahua test tool

8MPTVI, 8MP CVI / AHD, 8MP HD-SDI, EX-SDI

UTP, RJ45, TDR (optional), cable trace (optional),

Built-in, 2×1000M Ethernet ports

Built in, speed150M, wireless camera display.

8Gb SD card function

30 - 90% -10 - 50 °C

Auto 5 - 30 mins







IN / OUT INTERFACE

Video Interface

HDMI input

HDMI output

Stand Type

Colour

Audio Interface

Gross Weight

Power Supply

Battery

Battery life

Packing Dimensions

POWER IN

1 x BNC in, 1 x BNC out

Analogue video level meter, peak video signal level

SYNC level, colour burst chroma level

PTZ control RS485, baud rate 600 - 115200bps, Compatible with Pelco D/P, Samsung, Panasonic etc. One channel colour bar generator PAL/NTSC

1 channel HDMI input supports 1080P

1 channel HDMI output supports 1080P

57Wh polymer lithium battery, With 23W

After full charge (4-5 hours) normally 16 hours

charger, fully charged 4~5 hours

1 channel audio test function. Headphone socket

Desk type Blue

12v DC 2A

working time.

256mm x 159mm x 44mm

970g

OSD CONTROLS

Main function icons for: IP camera test, CVBS and HD camera test, Cable test, Media player, Tools, My Apps, User manual, Update. Select main icon to enter sub menu. Also icons for file explorer, settings and theme.

OSD LANGUAGE

English, Chinese, Korean, Russian, Italian, French, Polish, Spainish, Japanese, German, Turkish, Serbian, Czech, Portuguese.

ACCESSORIES

UK 12v DC charger, 3x carrying straps, BNC to BNC cable, DC 12v3A output cable, RS485 cable tester lead, audio test lead, RJ45 cable tester, carry case.

Tools: Network tool, PoE & power info, Quick Office, Data monitor, flashlight, calculator

My Apps: Rapid video, Rapid IP discovery, iVMS4500HD, gDMSS HD lite, VLC, EZ View, Droi Notes, XMEye

POWER OUT

DC 24V / 2A PoF DC 5v 2A DC12V/3A

Temporary camera supply, short circuit protection 48v PoE output max 25.5W USB out put as power bank only Temporary camera supply